

MIX ONE GALLON OF UNSCENTED HOUSEHOLD BLEACH WITH FOUR GALLONS OF WATER. POUR THIS SOLUTION DOWN THE WELL CASING (OR INTO THE SPRING BOX OR CISTERN.) MAKE SURE THE BLEACH SOLUTION HAS CONTACT WITH ALL INTERIOR SURFACES. THEN OPEN EACH FAUCET ASSOCIATED WITH THE WATER SUPPLY UNTIL YOU SMELL BLEACH. TURN THE FAUCETS OFF WHEN THE BLEACH IS DETECTED AND LEAVE THEM CLOSED FOR SEVERAL HOURS TO ALLOW IT CONTACT TIME WITH THE ENTIRE DISTRIBUTION SYSTEM.

THE BLEACH SOLUTION MUST BE COMPLETELY FLUSHED OUT OF THE SYSTEM BEFORE THE WATER CAN BE RESAMPLED. WITH NORMAL USAGE THIS USUALLY TAKES SEVERAL DAYS, DEPENDING ON THE VOLUME OF THE WATER SUPPLY. DO NOT REQUEST ANOTHER SAMPLE UNTIL YOU ARE CERTAIN THAT THE BLEACH IS COMPLETELY GONE.. THERE WILL BE A CHARGE FOR ANY UNNECESSARY TRIPS MADE BY THE SANITARIAN.